



# CENTERING AND SPREADING UNIT COMPACT CE

Devices for distension and centering the fabric.



## CENTERING AND SPREADING UNIT COMPACT CE

System for distension and centering the fabric.

|                                     |   |
|-------------------------------------|---|
| <b>overall dimensions L x H x W</b> | 375 x 890 x (RW+432) mm weight 350 Kg standard width<br>510 x 1140 x (RW+800) mm weight 800 Kg wider width            |
| <b>material</b>                     | carbon steel or stainless steel   |
| <b>color on painted steel</b>       | RAL 7021 for the structure RAL 9006 for side doors  |
| <b>rollers width</b>                | from 1600 mm to 4000 mm   |
| <b>fabric width</b>                 | from 1400 mm to 3800 mm   |
| <b>min working width</b>            | 400 mm  |
| <b>max working width</b>            | RW-200 mm   |
| <b>mechanical speed max</b>         | 150 m / min   |
| <b>max compressed air</b>           | 6 bar   |
| <b>voltage</b>                      | standard 3x400Vac-50Hz or others on request   |
| <b>standard auxiliary circuit</b>   | 24VDC   |
| <b>installed power</b>              | 2 Kw  |
| <b>ambient temperature</b>          | from 0 to + 55 °  |
| <b>noise</b>                        | <75db(A)  |
| <b>actuator type</b>                | pneumatic or electromechanical  |
| <b>fabric position control</b>      | alignment by means of ON/OFF photocell, bianco FTC7 proportional photocell, or by means of bianco FLUO optical reader |
| <b>electrical cabinet</b>           | independent or built into the system  |
| <b>optional for second roller</b>   | bow roller or dragging roller for delicate fabrics  |



www.bianco-spa.com

# PENDULAR GUIDE COMPACT CE

Devices for distension and centering the fabric.

